NBP05P2



Main Features

- Greater powers delivery capability
- System host board and add-on card
- Follows PICMG 1.3 mount holes and compatible with 4U chassis
- Supports:2 PClex16, 1 PClex4, 2 PCl
- Supports +12V, -12V, -5V, 3.3V power connector
- Compliance with PICMG1.3 CPU board : PIC688

Product Overview

The NBP05P2 is a 5-slot backplane with 1 SHB slot, 2 PCIex16, 1 PCIex4 and 2 PCI slot. And the PCIex16 slot support 1 PCIEx16 or 2 PCIex8 By auto detect, provide flexible expansion options. It follows PICMG 1.3 platform specifications and supports ATX power supply.

Specifications

System Architecture

5-slot backplane

Slots

- 1 SHB slot,
- 2 PCIex16 , 1 PCIex4 , 2 PCI

Power input

- 24 PIN ATX Power Connector
- 8 PIN ATX Standard Power Connector Support ±12V

Dimension

• 181.10 x 166.99 (mm)

Environment

- Board level operating temperatures: 0°C to 60°C
- **SE**orage temperatures: -20°C to 80°C
- 6-layer PCB to reduce noise and keep lower impedance

Relative humidity:

- 0% to 90% (operating, non-condensing)
- 0% to 95% (non-operating, non-condensing)

Certifications

- Œ approval
- **GEC** Class A

Dimension Drawing



